

# Technical datasheet

## LUKA-XL-730-1-C13300



### Product description

Luka emits reliably efficient light on traffic roads and industrial areas to support safety and security outdoors. The smart function also offers a range of smart city functions.

LED

220-240V  
50-60Hz

IP66

CCT  
3000 k


CRI  
70+

CLO


### Product technical data

|                       |                        |                            |                    |
|-----------------------|------------------------|----------------------------|--------------------|
| Mains voltage         | 220 - 240V AC, 50/60Hz | Ripple                     | 3 %                |
| Connection method     | Connection cable       | Inrush current             | 85 A               |
| Dimming type          | Non-dimmable           | Inrush time                | 256 µs             |
| IP rating             | 66                     | Optical system             | Lenses             |
| Protection class      | I                      | Optical part material      | Hardened glass     |
| Ambient temperature   | -40 to +40 °C          | Housing material           | Die-cast aluminium |
| Light source          | LED                    | Surface finish             | Powder coated      |
| Colour temperature    | 3000k                  | Service lifetime (L80 B10) | >100 000 h         |
| Color rendering index | 70                     | Warranty                   | 5 years            |
| Rated luminous flux   | 6,394 lm               |                            |                    |
| Connected load        | 56.50 W                |                            |                    |
| Luminous efficacy     | 113.2 lm/W             |                            |                    |

### Dimensions




### Light distribution



### Constant Light Output (CLO)

This system compensates for the depreciation of luminousflux to avoid excess lightingat the beginningof the installation's service life. Luminous depreciation over time must be taken into account to ensure a predefined lightinglevel duringthe luminaire's usefullife.

Without a CLO feature, this simply means increasingthe initial power upon installationin order tomake up for luminous depreciation. By precisely controlling the luminous flux,the energy needed to reach the required level can be maintained throughout the luminaire's life.




A. Dimming level  
B. Time

### MidNight function

The MidNight function feature allows an autonomous dimming without the need for an additional control line. The output levels can be set to 0% (OFF) or between 10% and 100% in steps of 1%

**Time-based:** The dimming profile defined in the reference schedule is referenced to the switchon time of the LED driver.

**Astro-based:** The dimming profile defined in the reference schedule is referenced to the annual average middle of the night, which is calculated based on the theoretical sunrise and sunset times.



1. Standard lighting level  
2. LED lighting consumption with CLO  
3. Energy savings