Product description

LINE Surface is an elegant linear LED luminaire with high-quality LED source with 50,000 hours lifetime and PMMA diffuser for uniform light. Available in 5 sizes (572-2820mm), color temperatures 3000K/4000K with CRI 80+/90+. DALI control option available. Ideal for offices and commercial spaces. 5-year warranty.

CRI 80+

| LED | 220-240 V 50-60 Hz | IP20 | | ϵ | CCT 4000 k | |
|-----|-----------------------|------|--|------------|---------------|--|
|-----|-----------------------|------|--|------------|---------------|--|

| Product technical data | | | | |
|------------------------|------------------------|----------------------------|---------------|--|
| Mains voltage | 220 - 240V AC, 50/60Hz | Ripple | 2 % | |
| Connection method | 3-phase track adapter | Inrush current | 18 A | |
| Dimming type | Non-dimmable | Inrush time | 44 µs | |
| IP rating | 20 | Optical system | Diffuser | |
| Protection class | I | Optical part material | РММА | |
| Ambient temperature | 0 to +25 °C | Housing material | Aluminium | |
| Light source | LED | Surface finish | Powder coated | |
| Colour temperature | 4000k | Width | 50.00 cm | |
| Color rendering index | 80 | Height | 70.00 cm | |
| Rated luminous flux | 7,275 lm | Length | 2,258.00 cm | |
| Connected load | 75.72 W | Weight | 5.50 kg | |
| Luminous efficacy | 96.1 lm/W | Service lifetime (L80 B10) | 50 000 h | |
| | | Warranty | 5 years | |
| | | • | | |
| Dimensions | | Light distribution | | |

