

# Technical datasheet

## HEXSUR-1200-M-840-2-WH




### Product description

The design of the luminaire returns to the power of the basic geometric shapes of the hexagon. By combining several diameters, it is possible to achieve different configurations and lighting scenarios with a great visual impact on the interior.

**LED** 220-240 V 50-60 Hz **IP20**  **CE** **CCT 4000 k** **CRI 80+**

### Product technical data

Mains voltage	220 - 240V AC, 50/60Hz	Ripple	1 %
Connection method	Plug-in terminal	DALI address	1
Dimming type	DALI	Standby power	0.50 W
IP rating	20	Inrush current	53 A
Protection class	I	Optical system	Diffuser
Ambient temperature	0 to +25 °C	Optical part material	PMMA
Light source	LED	Housing material	Aluminium
Colour temperature	4000k	Surface finish	Powder coated
Color rendering index	80	Width	1,200.00 cm
Rated luminous flux	5,640 lm	Height	70.00 cm
Connected load	54.75 W	Length	1,200.00 cm
Luminous efficacy	103.0 lm/W	Weight	6.40 kg
		Service lifetime (L80 B10)	50 000 h
		Warranty	5 years

### Dimensions

1200



d 1200 mm  
h 70 mm

### Light distribution

