

Technical datasheet

AREA-S-840-2-ASYM1



Product description

Area G3 is an ideal solution for most outdoor applications such as wall mounted around building facades, gardens, paths near to buildings, garages, entrance ways and drives.




LED 220-240 V IP66   CCT CRI
 50-60Hz 4000 k 80+

Product technical data

| | |
|-----------------------|------------------------|
| Mains voltage | 220 - 240V AC, 50/60Hz |
| Connection method | Connection cable |
| Dimming type | DALI |
| IP rating | 66 |
| Protection class | I |
| Impact rating | IK 08 |
| Ambient temperature | -30 to +35 °C |
| Light source | LED |
| Colour temperature | 4000k |
| Color rendering index | 80 |
| Rated luminous flux | 14,088 lm |
| Connected load | 100.00 W |
| Luminous efficacy | 140.9 lm/W |

| | |
|----------------------------|--------------------|
| DALI address | 1 |
| Inrush current | 90 A |
| Optical system | Lenses |
| Optical part material | Hardened glass |
| Housing material | Die-cast aluminium |
| Surface finish | Powder coated |
| Width | 246.00 cm |
| Height | 53.00 cm |
| Length | 292.00 cm |
| Weight | 2.50 kg |
| Service lifetime (L80 B10) | 50 000 h |
| Warranty | 5 years |

Dimensions



Light distribution

