## Product description

LINE Surface is an elegant linear LED luminaire with high-quality LED source with 50,000 hours lifetime and PMMA diffuser for uniform light. Available in 5 sizes (572-2820mm), color temperatures 3000K/4000K with CRI 80+/90+. DALI control option available. Ideal for offices and commercial spaces. 5-year warranty.

LED	220-240 V 50-60 Hz	<b>I</b> P <b>20</b>		C€	CCT 3000 k	CRI 90+
-----	-----------------------	----------------------	--	----	---------------	------------

Product technical data				
Mains voltage	220 - 240V AC, 50/60Hz	Ripple	1 %	
Connection method	3-phase track adapter	Inrush current	21 A	
Dimming type	Non-dimmable	Inrush time	132 μs	
IP rating	20	Optical system	Diffuser	
Protection class	I	Optical part material	РММА	
Ambient temperature	0 to +25 °C	Housing material	Aluminium	
Light source	LED	Surface finish	Powder coated	
Colour temperature	3000k	Width	50.00 cm	
Color rendering index	90	Height	70.00 cm	
Rated luminous flux	1,193 lm	Length	572.00 cm	
Connected load	16.22 W	Weight	1.23 kg	
Luminous efficacy	73.5 lm/W	Service lifetime (L80 B10)	50 000 h	
		Warranty	5 years	
Dimensions		Light distribution		

