

Technical datasheet

LINESUS2820-M-830-1-BL-DI/IND-



Product description

LINE Suspended is a pendant linear LED luminaire with high-quality LED source with 50,000 hours lifetime and PMMA diffuser. Available in 5 sizes (572-2820mm), color temperatures 3000K/4000K with CRI 80+/90+. Direct and indirect lighting options with DALI control available. Wide range of cable colors. Ideal for offices and commercial spaces. 5-year warranty.

LED

220-240 V  
50-60 Hz

IP20


CCT  
3000 k

CRI  
80+


Product technical data

|                       |                        |                            |               |
|-----------------------|------------------------|----------------------------|---------------|
| Mains voltage         | 220 - 240V AC, 50/60Hz | Ripple                     | 2 %           |
| Connection method     | Plug-in terminal       | Inrush current             | 55 A          |
| Dimming type          | Non-dimmable           | Inrush time                | 188 μs        |
| IP rating             | 20                     | Optical system             | Diffuser      |
| Protection class      | I                      | Optical part material      | PMMA          |
| Ambient temperature   | 0 to +25 °C            | Housing material           | Aluminium     |
| Light source          | LED                    | Surface finish             | Powder coated |
| Colour temperature    | 3000k                  | Width                      | 5.00 cm       |
| Color rendering index | 80                     | Height                     | 7.00 cm       |
| Rated luminous flux   | 5,358 lm               | Length                     | 282.00 cm     |
| Connected load        | 104.81 W               | Weight                     | 6.80 kg       |
| Luminous efficacy     | 107.2 lm/W             | Service lifetime (L80 B10) | 50 000 h      |
|                       |                        | Warranty                   | 5 years       |

Dimensions



Light distribution



Available cable colors

