

Technical datasheet

LINESUS2820-L-940-2-BL-DI-



Product description

LINE Suspended is a pendant linear LED luminaire with high-quality LED source with 50,000 hours lifetime and PMMA diffuser. Available in 5 sizes (572-2820mm), color temperatures 3000K/4000K with CRI 80+/90+. Direct and indirect lighting options with DALI control available. Wide range of cable colors. Ideal for offices and commercial spaces. 5-year warranty.

LED

220-240 V
50-60 Hz

IP20


CCT
4000 k

CRI
90+


Product technical data

Mains voltage	220 - 240V AC, 50/60Hz	Ripple	1 %
Connection method	Plug-in terminal	DALI address	1
Dimming type	DALI	Standby power	0.50 W
IP rating	20	Inrush current	53 A
Protection class	I	Optical system	Diffuser
Ambient temperature	0 to +25 °C	Optical part material	PMMA
Light source	LED	Housing material	Aluminium
Colour temperature	4000k	Surface finish	Powder coated
Color rendering index	90	Width	5.00 cm
Rated luminous flux	6,377 lm	Height	7.00 cm
Connected load	76.91 W	Length	282.00 cm
Luminous efficacy	82.9 lm/W	Weight	6.80 kg
		Service lifetime (L80 B10)	50 000 h
		Warranty	5 years

Dimensions



Light distribution



Available cable colors

