

Technical datasheet

WORTDUO-S-930-1-WAS-WH




Product description


Worker Track Duo is a linear LED luminaire for 3-phase track system with LED source with 50,000 hours lifetime. Available in 3 power options, color temperatures 3000K/4000K/5000K with CRI 80+/90+. Five light distribution types (50°, 80°, ASYM, SYM, WAS) with special optics reducing glare and DALI control option available. Provides comfortable and natural lighting with easy track system installation. Ideal for offices and stores. 5-year warranty.

LED 220-240 V IP20    UGR < 19 CCT 3000 k CRI 90+

Product technical data

| | | | |
|-----------------------|------------------------|----------------------------|---------------|
| Mains voltage | 220 - 240V AC, 50/60Hz | Ripple | 5 % |
| Connection method | 3-phase track adapter | Inrush current | 7 A |
| Dimming type | Non-dimmable | Inrush time | 28 μs |
| IP rating | 20 | Optical system | Lenses |
| Protection class | II | Optical part material | PMMA |
| Ambient temperature | 0 to +25 °C | Housing material | Aluminium |
| Light source | LED | Surface finish | Powder coated |
| Colour temperature | 3000k | Width | 44.00 cm |
| Color rendering index | 90 | Height | 53.00 cm |
| Rated luminous flux | 2,362 lm | Length | 1,122.00 cm |
| Connected load | 22.72 W | Weight | 2.80 kg |
| Luminous efficacy | 104.0 lm/W | Service lifetime (L80 B10) | 50 000 h |
| | | Warranty | 5 years |

Dimensions



Light distribution

