

Technical datasheet

TRIUM-S-840-1



Product description

Linear LED luminaire rated IP69K. Built for food processing and industrial facilities that clean with pressure and steam. 5-year warranty.

LED

220-240 V  
50-60 Hz

IP69k

CE

CRI  
80+

Product technical data

|                       |                        |                            |             |
|-----------------------|------------------------|----------------------------|-------------|
| Mains voltage         | 220 - 240V AC, 50/60Hz | Inrush current             | 15 A        |
| Connection method     | Connection cable       | Inrush time                | 260 µs      |
| IP rating             | 69k                    | Optical system             | Diffuser    |
| Protection class      | I                      | Optical part material      | PMMA        |
| Impact rating         | IK 10                  | Housing material           | Plastic     |
| Ambient temperature   | -20 to +45 °C          | Width                      | 81.00 cm    |
| Light source          | LED                    | Height                     | 81.00 cm    |
| Colour temperature    | 4000                   | Length                     | 1,200.00 cm |
| Color rendering index | 80                     | Weight                     | 1.90 kg     |
| Connected load        | 38.83 W                | Service lifetime (L70 B10) | 102 000 h   |
| Luminous efficacy     | 144.2 lm/W             | Warranty                   | 5 years     |

Dimensions



Light distribution

