# Technical datasheet

## BASETR-L-940-1-WH



### Product description

A track spotlight for retail stores, showrooms and exhibition spaces. A COB light source with CRI > 90 and two-axis adjustment let you aim light precisely at merchandise or displays. Black or white finish, for 3-phase track. Part of the Base range. Standard version without configuration, at a price that holds up in budget-driven projects.


LED 220-240V 50-60Hz IP20 CRI 90+

### Product technical data

| | |
|---|---|
| Mains voltage | 220 - 240V AC, 50/60Hz |
| Connection method | 3-phase track adapter |
| IP rating | 20 |
| Protection class | II |
| Ambient temperature | 0 to +25 °C |
| Light source | LED |
| Colour temperature | 4000 |
| Color rendering index | 90 |
| Connected load | 27.60 W |
| Luminous efficacy | 98.6 lm/W |

| | |
|---|---|
| Optical system | Lenses |
| Optical part material | PMMA |
| Housing material | Aluminium |
| Surface finish | Powder coated |
| Height | 160.00 cm |
| Diameter | 78.00 cm |
| Weight | 0.53 kg |
| Service lifetime (L80 B30) | 50 000 h |
| Warranty | 5 years |

### Dimensions




| | | |
|---|---|---|
| S | | |
| | H | 120 mm |
| | D | 60 mm |
| M | | |
| | H | 130 mm |
| | D | 65 mm |
| L | | |
| | H | 160 mm |
| | D | 78 mm |
| XL | | |
| | H | 158 mm |
| | D | 90 mm |

### Light distribution

