# Family datasheet

## Base Linear 65



### Product description

A linear luminaire for demanding environments. IP65 and IK08 ratings make it suitable for dusty, damp and cold conditions. A reliable choice for warehouses, workshops, garages and production halls. Part of the Base range. Standard version without configuration, at a price that holds up in budget-driven projects.


LED 220-240V 50-60Hz IP65

### Technical description

| | |
|---|---|
| Mains voltage | 220 - 240V AC, 50/60Hz |
| Connection method | Plug-in terminal |
| IP rating | 65 |
| Protection class | II |
| Impact rating | IK 08 |
| Light source | LED |
| Switching type | Non-dimmable |
| CRI | 80 |
| CCT | 4000K |
| Lumen output | 5040-9800 lm |
| Efficiency | Up to 140 lm/W |
| Power consumption | 36-70 W |

| | |
|---|---|
| Optical system | Diffuser |
| Optical part material | PC |
| Housing material | Plastic |
| Ambient temperature | 0 to +30°C |
| Service lifetime (L80 B30) | 80000h |
| Warranty | 5 years |


### Dimensions




**S**
L 1200 mm
W 70 mm
H 50 mm

**M/L**
L 1500 mm
W 70 mm
H 50 mm

### Light distribution curves



Default

## Product codes

The technical specifications of the luminaire are determined through the combination of these attributes, which result in a unique product code.

Order code example: **BASELIN-L-840-1**

| Attribute | Value | Code |
|---|---|---|
| Model | Base Linear 65 | BASELIN- |
| Version | S | S |
| | M | M |
| | L | L |
| CCT | 4000k (CRI 80+) | 840 |
| Dimming | Non-dimmable | 1 |