

Family datasheet

Base Linear 65



Product description

A linear luminaire for demanding environments. IP65 and IK08 ratings make it suitable for dusty, damp and cold conditions. A reliable choice for warehouses, workshops, garages and production halls. Part of the Base range. Standard version without configuration, at a price that holds up in budget-driven projects.

LED


220-240 V
50-60 Hz

IP65


Technical description

Mains voltage	220 - 240V AC, 50/60Hz	Optical system	Diffuser
Connection method	Plug-in terminal	Optical part material	PC
IP rating	65	Housing material	Plastic
Protection class	II	Ambient temperature	0 to +30°C
Impact rating	IK 08	Service lifetime (L80 B30)	80000h
Light source	LED	Warranty	5 years
Switching type	Non-dimmable		
CRI	80		
CCT	4000K		
Lumen output	5040-9800 lm		
Efficiency	Up to 140 lm/W		
Power consumption	36-70 W		

Dimensions



Light distribution curves



Product codes

The technical specifications of the luminaire are determined through the combination of these attributes, which result in a unique product code.

Order code example: BASELIN-L-840-1

Attribute	Value	Code
Model	Base Linear 65	BASELIN-
Version	S	S
	M	M
	L	L
CCT	4000k (CRI 80+)	840
Dimming	Non-dimmable	1